



Technical Information and Typical Properties

Sigma Stretch Film Performance 5™ 1.00 mil



Product Description

Performance5 is a high performance silage film that delivers high feed value efficiently and profitably. Quality and performance are consistent throughout

General

applications Big Squares In-line Round Bales High Speed
 Revision Date 6/22/2015 Available in 20 and 30 inch widths

Film Properties	Typical Value		Test Method
	(English)	Tolerance	
Tensile Strength at Yield MD	No Yield	--	ASTM D882
Tensile Strength at Yield TD	1240 psi	± 15%	ASTM D882
Tensile Strength at Break MD	4400 psi	± 15%	ASTM D882
Tensile Strength at Break TD	4000psi	± 15%	ASTM D882
Elongation at Break MD	430%	± 15%	ASTM D882
Elongation at Break TD	650%	± 15%	ASTM D882
Protrusion Puncture	17.5 lbs	± 15%	ASTM D5748
Protrusion Puncture Energy	17.5 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	450 g/mil	± 15%	ASTM D1922
Elmendorf Tear Strength TD	945 g/mil	± 15%	ASTM D1922
Cling - Outside to Inside @ 225%	min 200 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance
Core ID	3.05 inches	± 0.05 in
Film Thickness	25.4 micron	

Manufactured with pride in Canada by
Sigma Stretch Film of Canada
 219 Jamieson Bone Rd Belleville Ontario K8N-5A5
 Phone: 866-848-4400 • 613-966-2781
 Email: stretch.info@sigmaplastics.com
 Visit our website at www.sigmastretchfilm.com
 ©Copyright 2018 Sigma Stretch Film